

# Car Care Specialties, Inc

116 South Main Street, Unit # 2, Lodi, NJ 07644-2251    TECH SERVICE (973) 767-0035    FAX (973) 767-0038  
TOLL FREE ORDER LINE (877) 796-8300    WWW.CARCAREONLINE.COM

## PRODUCT LIST - 2010 BATTERMINDER - CAR CARE PRODUCTS

Product  
Number

Product  
Description



**BATTERYMINDER PLUS BATTERY MAINTAINER - 12 VOLT** - This is the next generation of computer-on-a-chip battery maintainers that automatically charges, conditions and maintains maintenance-free, deep cycle, marine and sealed gel 12 volt batteries with out overcharging. It is the first maintainer of its kind to reverse the primary cause of early battery failure known as sulphation. Batteries that were considered unrecoverable may now be brought back to useful condition. Press the button on the front of the unit to start the fully automatic de-sulphation process. The PulseMode circuitry creates high frequency pulses that break down sulphated crystals that form on older batteries. Prior to connecting the BatteryMinder, insure that the electrolyte is filled to recommended levels. The 12 foot long cord with the quick connect/disconnect/polarity plug end allows you to hook up or unplug in seconds. The kit includes a quick disconnect end/ring end terminal, that may be permanently attached to the battery in the car and a quick disconnect end/alligator clip terminal for use on a battery outside the car.

### 29204 BatteryMinder Plus Battery Maintainer-12 Volt



**BATTERYMINDER BATTERY COND. / MAINTAINER - 6 VOLT** - This is the next generation of computer-on-a-chip battery maintainers that automatically charges, conditions and maintains maintenance-free, deep cycle, marine and sealed gel 6 volt batteries with out overcharging. It is the first maintainer of its kind to reverse the primary cause of early battery failure known as sulphation. Batteries that were considered unrecoverable may now be brought back to useful condition. Press the button on the front of the unit to start the fully automatic de-sulphation process. The PulseMode circuitry creates high frequency pulses that break down sulphated crystals that form on older batteries. Prior to connecting the BatteryMinder, insure that the electrolyte is filled to recommended levels. The 12 foot long cord with the quick connect/disconnect/polarity plug end allows you to hook up or unplug in seconds. The kit includes a quick disconnect end/ring end terminal, that may be permanently attached to the battery in the car and a quick disconnect end/alligator clip terminal for use on a battery outside the car.

### 29205 BatteryMinder Battery Cond/Maintainer-6 Volt



**BATTERYMINDER 12 VOLT SOLAR BATTERY CHARGER / MAINTAINER / CONDITIONER** - 12 Volt - 5 Watt - This is the next generation of a solar powered computer-on-a-chip battery maintainer that automatically charges, conditions and maintains maintenance-free, deep cycle, marine and sealed gel 12 volt batteries without overcharging. The solar panel provides up to 5 watts of power with no external power supply. The combination is perfect for trailers, recreational vehicles, farm equipment or any other vehicle with no convenient power supply. It is the first maintainer of its kind to reverse the primary cause of early battery failure known as sulphation. Batteries that were once considered unrecoverable may now be brought back to useful condition. Press the button on the front of the unit to start the fully automatic de-sulphation process. The PulseMode circuitry creates high frequency pulses that break down sulphated crystals that form on older batteries. Prior to connecting the BatteryMinder, insure that the electrolyte is filled to recommended levels.

### 29221 12 Volt Solar Battery Charger/Maintainer/Conditioner



### **BATTERYMINDER QUICK CONNECT /DISCONNECT END /RING END TERMINAL**

- 24" Cord - If you have several vehicles that need either the BatteryMinder 12 or 6 volt and you wish to leave the terminal permanently attached to the battery, then this is just what you need. Loosen and remove the battery terminal clamp nut on the positive terminal and slide the red colored ring end over the bolt. Replace and tighten the terminal clamp nut to the proper torque. Loosen and remove the terminal clamp nut on the negative side and slide the blue colored ring end over the bolt. Replace and tighten the terminal clamp nut to the proper torque. The 24 inch wire may stay permanently attached to the battery. To hook up simply plug the quick connect/disconnect plug ends together and your battery is connected.

### 29297 Quick Connect /Disconnect End /Ring End Terminal