

Car Care Specialties, Inc

116 South Main Street, Unit # 2, Lodi, NJ 07644-2251 TECH SERVICE (973) 767-0035 FAX (973) 767-0038
TOLL FREE ORDER LINE (877) 796-8300 WWW.CARCAREONLINE.COM

PRODUCT LIST - 2010 SURFLEX - CAR CARE PRODUCTS



SURFLEX BLACK LEATHER/VINYL COLORANT - 8 OZ CAN - A water based, flexible, polymer aniline, surface colorant to restore the black color to both leather and vinyl that will not crack, chip or become brittle. Surfex restores the natural appearance to both leather and vinyl and does not leave a painted look like most lacquer based products. The black color is custom matched to the OEM European black and offers the same finish, durability and wear as the original surface finish. May be applied with a lint free cloth, brush or spray gun. The surface should be thoroughly cleaned with a citrus degreaser, rinsed with water and allowed to dry for 24 hours prior to application of the colorant. Do not use on suede. For best results, use between 70 and 90 degrees Fahrenheit.

11901 Surfex Black Leather/Vinyl Colorant - 8 oz Can



SURFLEX LEATHER "SOFFENER" - 8 OZ CAN - The most potent leather softener and restorer on the market. It softens old, stiff leather with a blend of natural and synthetic oils that are easily absorbed into the leather. Spray, brush or wipe onto the surface of the leather, cover with Saran Wrap or plastic and allow the oils to saturate and soften the leather fibers for 3-5 days. Repeat this process as many times as necessary, until the leather stops absorbing the oils. The leather is now restored to its potential. Contains no perfumes or fragrances and does not leave a residue. Use only to soften hard or stiff leather. Once the leather is restored switch to a quality leather conditioner to maintain the leather. Do not use on suede. For best results, use above 70 degrees Fahrenheit.

11951 Surfex Leather "Soffener" - 8 oz Can



SURFLEX FLEX-FILL CRACK ELIMINATOR - 4 OZ JAR - A neutral gray, cosmetic filling compound, specifically formulated to repair leather or vinyl. It air dries to a semi-flexible state that will fill blemishes, holes or repaired splits in leather and vinyl. Apply it like a wallboard spackle compound to fill the blemish, allow to dry, sand and/or score to match the leather grain and then recolor with Surfex Colorant. It is not a bonding agent, so if the leather is split through, a reinforcing patch must be glued to the underside of the leather with shoemakers glue. Flex-Fill may then be used to fill the split on top of the patch. Do not use on suede. For best results, use above 70 degrees Fahrenheit.

11961 Surfex Flex-Fill Crack Eliminator - 4 oz Jar